

Model

PSUIP 1x 2A 12VDC

Input Range	AC 100-240V rated 3Amp main fuse
Input Frequency	50/60Hz
Output Current	1 x 2A
Output Voltage	DC 12V
Fuse	Auto-reset PTC Fuse for each output, rated 2.5Amp
Surge Protected	Yes
Weight	0.5kgs
Case Type	Grey Polycarbonate
Operating Temp	- 10°C to 40°C
Storage Temp	- 20°C to +50°C
Operating Humidity	0% to 95% RH non condensing
Size	8cmx15cmx7.1cm (WxHxD)
IP Rating (when correctly installed)	IP66

Model

PSUIP 1X1A 24VAC

PSUIP 1X4A 24VAC

Input Range	AC 230V rated 3Amp main fuse	AC 220V rated 3Amp main fuse
Input Frequency	50Hz	50Hz
Output Current	1 x 1A	1 x 4A
Output Voltage	24VAC	24VAC
Fuse	Auto-reset PTC Fuse for each output, rated 1.35Amp	Auto-reset PTC Fuse for each output, rated 5Amp
Surge Protected	Yes	Yes
Weight	1.0Kg	2.8kg
Case Type	Grey Polycarbonate	Grey Polycarbonate
Operating Temp	- 10°C to 40°C	- 10°C to 40°C
Storage Temp	- 20°C to +50°C	- 20°C to +50°C
Operating Humidity	0% to 95% RH non condensing	0% to 95% RH non condensing
Size	9.5cmx25cmx6.2cm (WxHxD)	15cmx27cmx8.9cm (WxHxD)
IP Rating (when correctly installed)	IP66	IP66

