

Model	HAY- RMPSU1624 – 8A/1U	HAY- RMPSU1624-16A/2U
Input Range	AC 230V rated 3Amp main fuse	AC 230V rated 3Amp main fuse
Input Frequency	50/60Hz	50/60Hz
Supply Current	8 AMP	16 AMP
Rated Output Power	16 x 24VAC	16 x 24VAC
Fuse	Auto-reset PTC Fuse for each output, rated 1.1Amp	Auto-reset PTC Fuse for each output, rated 1.35Amp
Indicator	Individual LED indicator for each output	Individual LED indicator for each output
Mains switch	Yes	Yes
Voltage and Current Output LCD	No	No
Surge Protected	Yes	Yes
Regulated and Filtered	Yes	Yes
Weight	4.8kgs	6.3kgs
Case Type	19" 1U rack mount metal box, black powder coated	19" 2U rack mount metal box, black powder coated
Operating Temp	- 10°C to 50°C	- 10°C to 50°C
Storage Temp	- 20°C to +85°C	- 20°C to +85°C
Operating Humidity	0% to 90% RH non condensing	0% to 90% RH non condensing
Size	48cm x 4.6cm x 19cm (WxHxD)	48cm x 9cm x 19cm (WxHxD)
Cable Length	1.2m	1.2m
UK Plug & 2.1mm Socket	YES	YES

