

## Z3-4ADSN-4

### NDAA 3" IP PTZ with 4MP x4 zoom, with DDA Analytics and PoE+

The Z3-4ADSN-4 AI IP PTZ is an NDAA-compliant camera with impressive video quality and features. The Z3 provides basic connectivity options and standard motor speed while keeping a compact and sleek design. It can be installed almost anywhere with optional accessories and provides full compatibility with Provision-ISR's platforms (Ossia NVRs, Ossia VMS, Provision Cam2 Mobile App.)



## MAIN FEATURES

- Z3-4ADSN-4
- Sensor: 1/2.7" CMOS
- Resolution: 2560×1440 1-25/30FPS (4MP)
- Lens: X4 2.8mm (F1.6) - 12mm (F2.7)
- Compression: H.264/H.265/H264+/H265+/MJPEG
- True WDR (120dB)/HLC/BLC/3D-DNR
- True Day&Night - ICR
- Smart IR Distance: 50m
- Preset Speed: 50°/Sec
- Preset Accuracy: 0.1°
- Pan Range: 355°
- Tilt Range: 95°
- Preset Positions: 300
- 4 Patterns/8 Cruises/Park Action/Power Off Memory/Scheduled Tasks
- Alarm In/Out:1
- Audio In/Out:1
- SD Card: Event/Schedule Record (256GB)
- ONVIF: Yes
- IP66 Water-Proof
- Power Supply: PoE+ (802.3at) / DC12V±20%/2A (not included)
- Weight: ~1.2Kg



<https://provision-isr.com>

## SPECIFICATIONS

Video	
Image Sensor	1/2.7" CMOS
Effective Pixels	2560×1440
Sync System	Progressive Scan
Electronic Shutter	1/25~1/30,000s
Day & Night	ICR (Auto/Day/Night)
Min. Illumination	0.002 Lux (Color), 0.01 Lux (B&W), 0 Lux (IR On)

NDA Compliant	
NDA Compliant	Yes

Lens	
Optical Zoom	X4
Digital Zoom	No
Focal Length	2.8mm (F1.6) – 12mm (F2.7)
Aperture Range	F1.6 ~ F2.7
Focus	Auto/Manual
Minimum Focus Distance	0.3m
Horizontal Field of View	97°(wide) ~ 31°(tele)
Detect	2.8mm - 68m 12mm - 206m
Recognize	2.8mm - 13.6m 12mm - 41.3m
Identify	2.8mm - 6.8m 12mm - 20.7m

AI Features	
Analytics	AI: DDA Sterile Area, DDA Line Crossing General: Camera Tampering
Smart Tracking	Auto Tracking based on DDA (Human / Vehicle)
Face Recognition	No

<b>Face Database</b>	No
----------------------	----

## PTZ Features

<b>Pan Range</b>	355°
<b>Pan Speed</b>	Manual: 0.1~70°/s; Preset speed: 50°/s
<b>Tilt Range</b>	95°
<b>Tilt Speed</b>	Manual: 0.1~40°/s; Preset speed: 40°/s
<b>Presets</b>	300
<b>Patterns</b>	4 Tracks. Up to 3 minutes each
<b>Cruise</b>	8 cruises (16 presets per cruise)
<b>Scan</b>	Standard / Random (with left and right boundaries)
<b>Park Action</b>	Preset/Cruise/Pattern/Auto Scan/Random Scan
<b>Power Up Action</b>	Yes
<b>Schedule</b>	Up to 8 tasks (Preset/Cruise/Pattern/Auto Scan/Random Scan)
<b>3D Control</b>	Supported (Via Provision-ISR Devices)

## Image Enhancement

<b>Image Settings</b>	AWB Adjustable Exposure Mode Sharpness, Saturation, Brightness & Contrast Adjustable Auto Gain Adjustable
<b>WDR Range</b>	True WDR (120dB)
<b>BLC-HLC</b>	Yes
<b>3D-DNR Noise Reduction</b>	3D-DNR
<b>EIS</b>	N/A
<b>Defog</b>	No
<b>Image Orientation</b>	Mirror/Flip
<b>Dynamic Privacy Zone</b>	No

<b>Privacy Zone</b>	No
<b>Motion Detection</b>	Yes
<b>Audio</b>	
<b>Audio Compression</b>	G.711A/G.711U
<b>Communication</b>	2-Way Audio
<b>Housing</b>	
<b>IR Distance</b>	50m
<b>Illumination Type</b>	IR LED
<b>Wiper</b>	No
<b>Smart IR</b>	Yes
<b>Network</b>	RJ45
<b>Analog Video Output</b>	No
<b>Audio Input</b>	1Ch + Built-in Microphone
<b>Audio Output</b>	1Ch + Built-in Speaker
<b>SD Card</b>	Yes (microSD/SDHC/SDXC. Up to 256GB)
<b>RS-485</b>	No
<b>Alarm In</b>	1 Dry Contact
<b>Alarm Out</b>	1 Dry Contact
<b>Power Consumption</b>	Max 18.9W (With LED, Speaker, and Movement)
<b>Power Supply</b>	PoE+ (802.3at) / DC12V±20%/2A (not included)
<b>Work Environment</b>	-40°C ~ 65°C With IR off -40°C ~ 55°C with IR on
<b>Protection Rate</b>	IP66
<b>Fan &amp; Heater</b>	No

<b>Dimensions</b>	Φ 130mm × 162mm
<b>Weight (Gross)</b>	~1.2Kg
<b>Network</b>	
<b>Interface</b>	1 RJ45 10M/100M Adaptive Ethernet (Support PoE 802.3.at)
<b>User Access</b>	Supports simultaneous monitoring of up to 10 users with multi-stream real-time transmission
<b>Network Protocols</b>	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, HTTP POST
<b>ONVIF</b>	Yes
<b>Remote Monitoring</b>	IE Browsing (Plug-In required), Chrome/Edge/Safari/Firefox plug-in free browsing, Ossia VMS Software, Provision Cam2 Mobile App
<b>Compression</b>	
<b>Video Compression</b>	H.264/H.265/H264+/H265+/MJPEG
<b>Resolutions and Streams</b>	Main stream: 2560×1440 (4MP), 2304×1296 (3MP), 1920×1080 (2MP), 1280×720 (720P) Substream: 1280×720 (720P), 704×576 (D1), 352×288 (CIF) Third stream: 704×576 (D1), 480×240, 352×288 (CIF)
<b>FPS</b>	1-25/30FPS
<b>Bit-Rate</b>	1536Kbps ~ 7192Kbps@H.265 / 2048Kbps ~ 8192Kbps@H.264
<b>Encode Mode</b>	VBR/CBR
<b>Image Quality</b>	Five levels under VBR; Free adjustment under CBR