# PR-WS15W-IP

## IP ONVIF 15W Indoor wall speaker

Compact and efficient, this 15W indoor IP horn speaker delivers crystal-clear audio with a powerful sound output of 101dB, ensuring announcements and alerts are heard with clarity. Ideal for indoor spaces, it combines high-performance audio with easy installation.

| Built In 15W Amplifier | 101 dB | IP55 Protection rating |
|---|---|---|

## MAIN FEATURES

• PR-WS15W-IP IP ONVIF 15W Indoor wall speaker
• Amplifier: Built-in 15W Amplifier
• Max SPL: 101dB
• Frequency Response: 80Hz~20KHz
• Installation: Wall Mount
• Power: DC12V / PoE~1.25Amp

• Power Consumption: 15W Max
• Operation Temperature: -30-60°C
• Protection Rate: IP55
• Dimensions: 296*196*157mm (W x H x D)
• Net Weight: ~3Kg
• Power supply not included

https://provision-isr.com

# PR-WS15W-IP

## SPECIFICATIONS

| Speaker | |
|---|---|
| **Max SPL** | 101dB |
| **Frequency Response** | 80Hz~20KHz |

| Audio | |
|---|---|
| **Usage** | Real-Time Audio Broadcast / Up to 10 pre-loaded files (Triggered by API) |
| **Codec** | OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz |

| Amplifier | |
|---|---|
| **Amplifier** | Built-in 15W Amplifier |

| Network | |
|---|---|
| **Protocols** | SIP, ONVIF, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NTP, Multicast |
| **VoIP** | 2 SIP Accounts SIP Direct IP Call RTP Multicast |
| **Security** | Password protection, IP address filtering, Digest authentication, User access log |
| **Onvif** | Profile S |
| **Interface** | 10/100 Base-TX, RJ45 |

| GENERAL | |
|---|---|
| **Power** | DC12V / PoE~1.25Amp |
| **Power Consumption** | 15W Max |
| **Protection Rate** | IP55 |
| **Installation** | Wall Mount |
| **Dimensions** | 296*196*157mm (W x H x D) |
| **Net Weight** | ~3Kg |
| **Operation Temperature** | -30-60°C |